

# FLEXBLOC™ Ordering Guide



Gear Unit		FLEXBLOC™ Size	Reducer Options	Input Option	Motor	Motor Options																												
<b>SK</b>						see pages 222 - 233																												
<table border="1"> <thead> <tr> <th>FLEXBLOC™ Design</th> </tr> </thead> <tbody> <tr> <td>1SI</td> </tr> </tbody> </table>		FLEXBLOC™ Design	1SI	<table border="1"> <thead> <tr> <th>FLEXBLOC™ Size</th> </tr> </thead> <tbody> <tr><td><input type="radio"/> 31</td></tr> <tr><td><input type="radio"/> 40</td></tr> <tr><td><input type="radio"/> 40/31</td></tr> <tr><td><input type="radio"/> 50</td></tr> <tr><td><input type="radio"/> 50/31</td></tr> <tr><td><input type="radio"/> 63</td></tr> <tr><td><input type="radio"/> 63/31</td></tr> <tr><td><input type="radio"/> 75</td></tr> <tr><td><input type="radio"/> 75/40</td></tr> </tbody> </table> <table border="1"> <thead> <tr> <th>Shafts</th> </tr> </thead> <tbody> <tr><td><input type="radio"/> Inch</td></tr> <tr><td><input type="radio"/> Metric</td></tr> </tbody> </table>	FLEXBLOC™ Size	<input type="radio"/> 31	<input type="radio"/> 40	<input type="radio"/> 40/31	<input type="radio"/> 50	<input type="radio"/> 50/31	<input type="radio"/> 63	<input type="radio"/> 63/31	<input type="radio"/> 75	<input type="radio"/> 75/40	Shafts	<input type="radio"/> Inch	<input type="radio"/> Metric	<table border="1"> <thead> <tr> <th>Reducer Options</th> </tr> </thead> <tbody> <tr> <td><input type="checkbox"/> <b>V</b> - Plug in Solid Output Shaft  30</td> </tr> <tr> <td><input type="radio"/> VA <input type="radio"/> VB <input type="radio"/> Unassembled</td> </tr> <tr> <td><input type="checkbox"/> <b>L</b> - Double Solid Shaft Extension  31</td> </tr> <tr> <td><input type="checkbox"/> <b>F</b> - B5 Output Flange  31</td> </tr> <tr> <td><input type="radio"/> FA <input type="radio"/> FB <input type="radio"/> FF <input type="radio"/> Unassembled</td> </tr> <tr> <td><input type="checkbox"/> <b>D</b> - Torque Arm  31</td> </tr> <tr> <td><input type="radio"/> DA <input type="radio"/> DB <input type="radio"/> Unassembled</td> </tr> <tr> <td><input type="checkbox"/> <b>H</b> - Shaft Cover  30</td> </tr> <tr> <td><input type="radio"/> HA <input type="radio"/> HB <input type="radio"/> Unassembled</td> </tr> <tr> <td><input type="checkbox"/> <b>X</b> - Foot Plate  31</td> </tr> <tr> <td><input type="checkbox"/> <b>J</b> - Shaft Bushing ____ size  31</td> </tr> <tr> <td><input type="checkbox"/> <b>H10</b> - Helical Input Stage (10:1)  33</td> </tr> </tbody> </table>	Reducer Options	<input type="checkbox"/> <b>V</b> - Plug in Solid Output Shaft  30	<input type="radio"/> VA <input type="radio"/> VB <input type="radio"/> Unassembled	<input type="checkbox"/> <b>L</b> - Double Solid Shaft Extension  31	<input type="checkbox"/> <b>F</b> - B5 Output Flange  31	<input type="radio"/> FA <input type="radio"/> FB <input type="radio"/> FF <input type="radio"/> Unassembled	<input type="checkbox"/> <b>D</b> - Torque Arm  31	<input type="radio"/> DA <input type="radio"/> DB <input type="radio"/> Unassembled	<input type="checkbox"/> <b>H</b> - Shaft Cover  30	<input type="radio"/> HA <input type="radio"/> HB <input type="radio"/> Unassembled	<input type="checkbox"/> <b>X</b> - Foot Plate  31	<input type="checkbox"/> <b>J</b> - Shaft Bushing ____ size  31	<input type="checkbox"/> <b>H10</b> - Helical Input Stage (10:1)  33			
FLEXBLOC™ Design																																		
1SI																																		
FLEXBLOC™ Size																																		
<input type="radio"/> 31																																		
<input type="radio"/> 40																																		
<input type="radio"/> 40/31																																		
<input type="radio"/> 50																																		
<input type="radio"/> 50/31																																		
<input type="radio"/> 63																																		
<input type="radio"/> 63/31																																		
<input type="radio"/> 75																																		
<input type="radio"/> 75/40																																		
Shafts																																		
<input type="radio"/> Inch																																		
<input type="radio"/> Metric																																		
Reducer Options																																		
<input type="checkbox"/> <b>V</b> - Plug in Solid Output Shaft  30																																		
<input type="radio"/> VA <input type="radio"/> VB <input type="radio"/> Unassembled																																		
<input type="checkbox"/> <b>L</b> - Double Solid Shaft Extension  31																																		
<input type="checkbox"/> <b>F</b> - B5 Output Flange  31																																		
<input type="radio"/> FA <input type="radio"/> FB <input type="radio"/> FF <input type="radio"/> Unassembled																																		
<input type="checkbox"/> <b>D</b> - Torque Arm  31																																		
<input type="radio"/> DA <input type="radio"/> DB <input type="radio"/> Unassembled																																		
<input type="checkbox"/> <b>H</b> - Shaft Cover  30																																		
<input type="radio"/> HA <input type="radio"/> HB <input type="radio"/> Unassembled																																		
<input type="checkbox"/> <b>X</b> - Foot Plate  31																																		
<input type="checkbox"/> <b>J</b> - Shaft Bushing ____ size  31																																		
<input type="checkbox"/> <b>H10</b> - Helical Input Stage (10:1)  33																																		
<table border="1"> <thead> <tr> <th>Input Shaft</th> <th>NEMA Adapter</th> <th>IEC</th> </tr> </thead> <tbody> <tr> <td><b>W</b></td> <td><b>N48C</b> <b>N56C</b> <b>N140TC</b> <b>N180TC</b></td> <td><b>IEC 63</b> <b>IEC 71</b> <b>IEC 80</b> <b>IEC 90</b> <b>IEC 100</b> <b>IEC 112</b></td> </tr> </tbody> </table>		Input Shaft	NEMA Adapter	IEC	<b>W</b>	<b>N48C</b> <b>N56C</b> <b>N140TC</b> <b>N180TC</b>	<b>IEC 63</b> <b>IEC 71</b> <b>IEC 80</b> <b>IEC 90</b> <b>IEC 100</b> <b>IEC 112</b>	<table border="1"> <thead> <tr> <th>Motors</th> <th>Premium Efficient Motors</th> </tr> </thead> <tbody> <tr> <td><b>63S/4</b> - 0.16hp</td> <td><b>80LP/4</b> - 1hp</td> </tr> <tr> <td><b>63L/4</b> - 0.25hp</td> <td><b>90SP/4</b> - 1.5hp</td> </tr> <tr> <td><b>71S/4</b> - 0.33hp</td> <td><b>90LP/4</b> - 2hp</td> </tr> <tr> <td><b>71L/4</b> - 0.50hp</td> <td><b>100LP/4</b> - 3hp</td> </tr> <tr> <td><b>80S/4</b> - 0.75hp</td> <td><b>112MP/4</b> - 5hp</td> </tr> </tbody> </table>		Motors	Premium Efficient Motors	<b>63S/4</b> - 0.16hp	<b>80LP/4</b> - 1hp	<b>63L/4</b> - 0.25hp	<b>90SP/4</b> - 1.5hp	<b>71S/4</b> - 0.33hp	<b>90LP/4</b> - 2hp	<b>71L/4</b> - 0.50hp	<b>100LP/4</b> - 3hp	<b>80S/4</b> - 0.75hp	<b>112MP/4</b> - 5hp													
Input Shaft	NEMA Adapter	IEC																																
<b>W</b>	<b>N48C</b> <b>N56C</b> <b>N140TC</b> <b>N180TC</b>	<b>IEC 63</b> <b>IEC 71</b> <b>IEC 80</b> <b>IEC 90</b> <b>IEC 100</b> <b>IEC 112</b>																																
Motors	Premium Efficient Motors																																	
<b>63S/4</b> - 0.16hp	<b>80LP/4</b> - 1hp																																	
<b>63L/4</b> - 0.25hp	<b>90SP/4</b> - 1.5hp																																	
<b>71S/4</b> - 0.33hp	<b>90LP/4</b> - 2hp																																	
<b>71L/4</b> - 0.50hp	<b>100LP/4</b> - 3hp																																	
<b>80S/4</b> - 0.75hp	<b>112MP/4</b> - 5hp																																	

Other Pole & Speed Options available

## Product Specifications

Single Worm	Helical Worm (1SI_/H10)		Double Worm (1SI_/_)		Paint	Torque Arm Orientation (If Selected)			
Ratio	Ratio	Position	Ratio	Position					
<input type="radio"/> 5	<input type="radio"/> 50	<input type="radio"/> T1	<input type="radio"/> 150	<input type="radio"/> U1	<input type="radio"/> No Paint (Standard)				
<input type="radio"/> 7.5	<input type="radio"/> 75	<input type="radio"/> T2	<input type="radio"/> 225	<input type="radio"/> U2	<input type="radio"/> Stainless Steel Paint				
<input type="radio"/> 10	<input type="radio"/> 100	<input type="radio"/> T3	<input type="radio"/> 300	<input type="radio"/> U3	<input type="radio"/> Special _____				
<input type="radio"/> 12.5	<input type="radio"/> 125	<input type="radio"/> T4	<input type="radio"/> 375	<input type="radio"/> U4					
<input type="radio"/> 15	<input type="radio"/> 150		<input type="radio"/> 450	<input type="radio"/> U5					
<input type="radio"/> 20	<input type="radio"/> 200		<input type="radio"/> 600	<input type="radio"/> U6					
<input type="radio"/> 25	<input type="radio"/> 250		<input type="radio"/> 750	<input type="radio"/> U7					
<input type="radio"/> 30	<input type="radio"/> 300		<input type="radio"/> 900	<input type="radio"/> U8					
<input type="radio"/> 40	<input type="radio"/> 400		<input type="radio"/> 1200						
<input type="radio"/> 50	<input type="radio"/> 500		<input type="radio"/> 1500						
<input type="radio"/> 60	<input type="radio"/> 600		<input type="radio"/> 1800						
<input type="radio"/> 80	<input type="radio"/> 800		<input type="radio"/> 2400						
<input type="radio"/> 100	<input type="radio"/> 1000		<input type="radio"/> 3000						
					<table border="1"> <thead> <tr> <th>Torque Arm Orientation (If Selected)</th> </tr> </thead> <tbody> <tr> <td><input type="radio"/> Side A </td> </tr> <tr> <td><input type="radio"/> Side B </td> </tr> </tbody> </table>		Torque Arm Orientation (If Selected)	<input type="radio"/> Side A	<input type="radio"/> Side B
Torque Arm Orientation (If Selected)									
<input type="radio"/> Side A									
<input type="radio"/> Side B									

## Gearmotor Only Details

Voltage & Frequency	Terminal Box Position	Conduit Entry Location
<input type="radio"/> 208V-60Hz <input type="radio"/> 230/460V-60Hz <input type="radio"/> 575V-60Hz <input type="radio"/> 400V-50Hz <input type="radio"/> Other _____	<input type="radio"/> KK1 <input type="radio"/> KK2 <input type="radio"/> KK3 <input type="radio"/> KK4	<input type="radio"/> I * <input type="radio"/> II <input type="radio"/> III * <input type="radio"/> IV
* Brakemotor options		